



LEVELLER 5T | 10T | 20T



LIFTINGXPERTS.COM

TECHNICAL DETAILS

Max. work load	5000 - 10.000 - 20.000 KG
Levelling capacity	1250 - 1500 - 3000 KG
Standard chain length	4,0 metres
Max. load angle	60°
Lighting	2 x 40 W 4000 lm
Supplied incl. CU/EC declaration and certificate.	

OPTIONAL EXTRAS

- Protective cover
- Rubber stopper
- Chain length made to size
- Extra batteries
- Spare hand transmitter

CONTROL

- 12v hydraulically controlled system
- Radiographic operation
- Working on 2.4 GHz
- Maximum 100 m transmission range

REQUIREMENTS CONCERNING THE ENVIRONMENT

- Ambient temperatures between -20 and +55



LEVELLER 5 TON

Height	607 mm
Length	432 mm
Width	355 mm

LEVELLER 10 TON

Height	737 mm
Length	632 mm
Width	466 mm

LEVELLER 20 TON

Height	831 mm
Length	702 mm
Width	475 mm



LEVELLER 5T | 10T | 20T

LiftingXperts LEVELLER is suitable for levelling loads at a lifting angle of a maximum of 60 degrees. Thanks to the intelligent design the LEVELLER is suitable for hoisting in narrow conditions.

The LEVELLER is simple to operate with the hand transmitter supplied. The intelligent design with safety button, light button and 2 rotation buttons makes the LEVELLER extremely user-friendly. The hand transmitter also has a range of no less than 100 metres.

The LEVELLER has LED work lighting on bottom side so there is always sufficient light when fitting stairs in shafts or when working on dark days.





VAN SOEST

van Soest B.V.
Morsestraat 17, 4004 JP Tiel

www.vansoest-bv.nl
info@vansoest-bv.nl
0344-610607

L I F T I N G X P E R T S . C O M